


# Material Safety Data Sheet

Dr. Jean Bausch KG  
Oskar-Schindler-Str. 4  
50769 Cologne - Germany  
Phone: ++49-221-70936-0  
Fax: ++49-221-70936-66  
Internet: www.bauschdental.de  
eMail: info@bauschdental.de

**US-Sales Office:**  
**Bausch Articulating Papers Inc.**  
12 Murphy Drive, Unit 4  
Nashua, NH 03062 - U.S.A  
Phone & Fax: (603) 883-2155  
Internet: www.bauschdental.com  
eMail: info@bauschdental.com



## Identity (As Used on Label and List)

**Trade Name:** Bausch Articulating Paper 40 $\mu$  extra thin blue

**Code:** BK 61 precut strips, BK 17 Horseshoeshape

**Chemical Description:** Castor Oil (Pharmaceutical Quality), cellulose (Paper oxigene bleached), C.I. Pigment blue 27, Tech Binder (mixed polymerization of artificial substance)

**Product Use:** Dental Material, for Marking of Occlusal Surface

## Section I

Manufacturer's Name <b>Dr. Jean Bausch KG</b>	Emergency Telephone Number ++49-221-70936-0, (603) 883-2155
Address (Number, Street, City, State, and Zip Code) Oskar-Schindler-Str. 4 50769 Cologne-Germany Bausch Articulating Papers Inc. 12 Murphy Drive, Unit 4 Nashua NH, 03062 -U.S.A	Telephone Number for Information ++49-221-70936-0, (603) 883-2155
	Date Prepared 11.02.1999
	Signature of Preparer (optional) Peter Bausch

## Section II - Hazardous Ingredients / Identity Information

Hazardous Components (Specific Chemical Identity; Common Name(s))	OSHA PEL	ACGIH TLV	Other Limits Recommended	% (optional)
none				

## Section III - Physical / Chemical Characteristics

Boiling Point n.a.	Specific Gravity (H2O) = 1) 0.91 (D)	Melting Point
Vapor Pressure (mm Hg.) n.a.	Vapor Density (AIR=1) n.a.	Evaporation Rate (Butyl Acetate = 1) n
Solubility in Water none	Appearance and Odor blue strips, sheets, and rolls of paper	

## Section IV - Fire and Explosion Hazard Data

Flash Point (Method Used) > 300°C (572°F) (Literature)	Flammable Limits	LEL n.a.	UEL n.a.
---	------------------	-------------	-------------

### Extinguishing Media

Use dry chemicals or carbon dioxide; water may be ineffective, but should be used to keep fire exposed containers cool.

### Special Fire Fighting Procedures

not required

### Unusual Fire and Explosion Hazards

Firefighters should wear self-contained breathing apparatus in the positive pressure mode with a full facepiece when there is a possibility of exposure to smoke, fumes, or hazardous decomposition products.