

SECTION 4 - FIRE AND EXPLOSION DATA

FLASH POINT: 252°C closed cup FLAMMABLE LIMITS: N.E.

EXTINGUISHING MEDIA: Dry Chemical, Carbon Dioxide, Alcohol Foam

SPECIAL FIRE FIGHTING PROCEDURES: Water is not effective medium. Firefighters should wear self contained breathing apparatus and full protective clothing.

UNUSUAL FIRE AND EXPLOSION HAZARDS: Irritating and/or toxic aerosols or gases may be present.

HAZARDOUS COMBUSTION PRODUCTS: Carbon Dioxide, Carbon Monoxide, Sulfur Hydrogen Sulfide

=====

SECTION 5 - REACTIVITY DATA

STABILITY: STABLE: X UNSTABLE: POLYMERIZATION: WILL NOT OCCUR: X WILL OCCUR:

CONDITIONS TO AVOID: High temperatures (> 121°C); open flames

INCOMPATIBILITY (MATERIALS TO AVOID): Strong acids, bases, oxidizers.

HAZARDOUS DECOMPOSITION OR BY-PRODUCTS: N.E.

=====

SECTION 6 - HEALTH HAZARD DATA and FIRST AID INFORMATION

	YES	NO	NE	NA	NTP	IARC	OSHA	OTHER
MUTAGENIC AFFECTS:		X						
TERATOGENIC AFFECTS:		X						
REPRODUCTIVE TOXIN:		X						
CARCINOGENICITY:	X				(as Silica dust)		X	
SENSITIZER:		X						

ROUTES OF ENTRY: INHALATION X SKIN X INGESTION X

HEALTH HAZARD: (ACUTE AND CHRONIC): Breathing vapor generated from this product may be irritating to the eyes, nose and throat.

SIGNS AND SYMPTOMS OF OVEREXPOSURE: Headaches

CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE: N.E.

=====

SECTION 6 - HEALTH HAZARD DATA and FIRST AID INFORMATION - continued

EMERGENCY FIRST AID PROCEDURES:

INHALATION: Remove to fresh air if irritation develops

EYES: Flush with large volumes of water, consult a physician if irritation develops.

SKIN: Wash thoroughly with soap and water

INGESTION: Do not induce vomiting. Dilute by drinking several glasses of water. Seek medical attention.

=====

SECTION 7 - PRECAUTIONS FOR SAFE HANDLING AND USE

IN CASE OF RELEASE OR SPILL:

Absorb with inert material; transfer to container for disposal

WASTE DISPOSAL METHOD:

Land fill per local and Federal Regulations

STORAGE, HANDLING, AND SPECIAL PRECAUTIONS:

Store at normal room temperature in a well ventilated area

=====

SECTION 8 - CONTROL MEASURES

RESPIRATORY PROTECTION: N.A.

VENTILATION: LOCAL EXHAUST: Recommended MECHANICAL: N.E.
SPECIAL: N.E. OTHER: N.E.

PROTECTIVE GLOVES: Synthetic/Vinyl Gloves

EYE PROTECTION: Safety glasses or goggles

OTHER PROTECTIVE CLOTHING OR EQUIPMENT: N.E.

WORK/HYGIENIC PRACTICE: N.E.

=====

SECTION 9 - PREPARATION INFORMATION

This data is supplied to comply with OSHA Hazard Communication Standard 29 CFR 1910,1200 and W.H.M.I.S. CPR

PREPARED BY: T. Joritz
Director Regulatory Affairs

Date: 07 March 2001

=====

N.A. = NOT APPLICABLE
N.E. = NOT ESTABLISHED

The information herein is given in good faith but no warranty expressed or implied is made.

=====

		NFPA	
FIRE 1	TOXICITY 1	REACTIVITY 1	SPECIAL -

=====

MATERIAL SAFETY DATA SHEET

SECTION 1 - SOURCE/IDENTITY/USE INFORMATION

MANUFACTURER	SUPPLIER
GC AMERICA INC.	
3737 West 127th St.	
Alsip, Illinois, 60803	
Telephone: 708-597-0900	
Hours: Mon.- Fri. 8:00 am. - 5:00 pm. C.S.T.	
Transportation Emergency No. 800-424-9300	

COMMON NAME:

- EXAFLEX BASE: INJECTION/REGULAR/MONOPHASE/HEAVY BODY
- EXAMIX BASE: INJECTION/REGULAR/MONOPHASE/HEAVY BODY - CARTRIDGE
- EXAMIX NDS BASE: INJECTION/REGULAR/MONOPHASE/HEAVY BODY - CARTRIDGE
- EXAFAST NDS BASE: INJECTION/REGULAR/MONOPHASE/HEAVY BODY - CARTRIDGE

Chemical Name: N.A.

PRODUCT USE: Dental Impression Material

The following information is provided with regard to the toxicity and hazards the pure components present in this portion of the unmixed two paste system

=====

SECTION 2 - HAZARDOUS INGREDIENTS/IDENTITY INFORMATION

COMPONENT AND C.A.S.	EXPOSURE LIMITS	LD50/LC50	% _____
Silica-Amorphous 112926-00-8	PEL = 10.0 mg/m ³ TLV/TWA = 10.0 mg/m ³ (as dust) (ACGIH)	N.E.	35-55%
Vinyl Dimethyl Poly -Dimethyl Siloxane 68083-19-2	N.E.	N.E.	35-60%
Polydimethyl Siloxane (not listed) (SiH Terminated)	N.E.	LD50= 5mg/m ³ (oral rat) LC50= N.E.	1-20%

=====

SECTION 3 - PHYSICAL/CHEMICAL PROPERTIES

BOILING POINT: 160°C SPECIFIC GRAVITY: (H₂O=1) 1.35g/cm³
 VAPOR PRESSURE: 100/50°C MELTING POINT: N.E.
 VAPOR DENSITY: 2.56 EVAPORATION RATE: N.E.
 SOLUBILITY IN WATER: Insoluble ODOR THRESHOLD: N.E.
 COEFFICIENT OF OIL/WATER DISTRIBUTION: N.E.
 APPEARANCE AND ODOR: Yellow odorless paste/putty

SECTION 4 - FIRE AND EXPLOSION DATA

FLASH POINT: 252°C closed cup FLAMMABLE LIMITS: N.E.

EXTINGUISHING MEDIA: Dry Chemical, Carbon Dioxide, Alcohol Foam

SPECIAL FIRE FIGHTING PROCEDURES:

Water is not effective medium. Firefighters should wear self contained breathing apparatus and full protective clothing.

UNUSUAL FIRE AND EXPLOSION HAZARDS:

Irritating and/or toxic aerosols or gases may be present.

HAZARDOUS COMBUSTION PRODUCTS:

Carbon Dioxide, Carbon Monoxide, Sulfur Hydrogen Sulfide

SECTION 5 - REACTIVITY DATA

STABILITY: STABLE: X UNSTABLE:
 POLYMERIZATION: WILL NOT OCCUR: X WILL OCCUR:

CONDITIONS TO AVOID: High temperatures (> 121°C); open flames

INCOMPATIBILITY (MATERIALS TO AVOID): Strong acids, bases, oxidizers.

HAZARDOUS DECOMPOSITION OR BY-PRODUCTS: N.E.

SECTION 6 - HEALTH HAZARD DATA and FIRST AID INFORMATION

	YES	NO	NE	NA	NTP	IARC	OSHA	OTHER
MUTAGENIC AFFECTS:		X						
TERATOGENIC AFFECTS:		X						
REPRODUCTIVE TOXIN:		X						
CARCINOGENICITY:		X	(as Silica dust)			X		
SENSITIZER:		X						

ROUTES OF ENTRY: INHALATION X SKIN X INGESTION X

SECTION 9 - PREPARATION INFORMATION

This data is supplied to comply with OSHA Hazard Communication Standard 29 CFR 1910,1200 and W.H.M.I.S. CPR

PREPARED BY: T. Joritz
Director Regulatory Affairs

Date: 07 March 2001

=====

N.A. = NOT APPLICABLE
N.E. = NOT ESTABLISHED

The information herein is given in good faith but no warranty expressed or implied is made.

=====

		NFPA	
FIRE 1	TOXICITY 1	REACTIVITY 1	SPECIAL -

=====			

MATERIAL SAFETY DATA SHEET

SECTION 1 - SOURCE/IDENTITY/USE INFORMATION

MANUFACTURER SUPPLIER
 GC AMERICA INC.
 3737 West 127th St.
 Alsip, Illinois, 60803
 Telephone: 708-597-0900
 Hours: Mon.- Fri. 8:00 am. - 5:00 pm. C.S.T.
 Transportation Emergency Telephone No. 800-424-9300

COMMON NAME: EXAFLEX PUTTY BASE AND CATALYST
 EXAFLEX PUTTY BASE AND CATALYST

Chemical Name: N.A.

PRODUCT USE: Dental Impressions

The following information is provided with regard to the toxicity and hazards of the pure components present in this portion of the unmixed two paste system.

=====

SECTION 2 - HAZARDOUS INGREDIENTS/IDENTITY INFORMATION

COMPONENT AND C.A.S.	EXPOSURE LIMITS	LD50/LC50	%
Polydimethyl Siloxane (not listed)	N.E.	LD50 = 5mg/m ³ (oral rat)	11%
Vinyl Dimethyl Polydimethyl Siloxane 68083-19-2	N.E.	N.E.	11%
Silicon Dioxide 112926-00-8	PEL = 0.1mg/m ³ TLV/TWA = 0.1mg/m ³ (as dust) (ACGIH)	N.E.	78%

=====

SECTION 3 - PHYSICAL/CHEMICAL PROPERTIES

BOILING POINT: 160°C SPECIFIC GRAVITY (H₂O = 1): 1.67
 VAPOR PRESSURE: 100/50°C MELTING POINT: N.E.
 VAPOR DENSITY: 2.56 EVAPORATION RATE: N.E.
 SOLUBILITY IN WATER Insoluble ODOR THRESHOLD: N.A.
 COEFFICIENT OF OIL/WATER DISTRIBUTION: N.E.
 APPEARANCE AND ODOR: A yellow or blue paste. Both are odorless.

=====

MATERIAL SAFETY DATA SHEET

SECTION 1 - SOURCE/IDENTITY/USE INFORMATION

MANUFACTURER

GC AMERICA INC.

3737 West 127th St.

Alsip, Illinois, 60803

Telephone: 708-597-0900

Hours: Mon.- Fri. 8:00 am. - 5:00 pm. C.S.T.

Transportation Emergency No. 800-424-9300

COMMON NAME:

EXAFLEX CATALYST: INJECTION/REGULAR/MONOPHASE/HEAVY BODY

EXAMIX CATALYST: INJECTION/REGULAR/MONOPHASE/HEAVY BODY - CARTRIDGE

EXAMIX NDS CATALYST: INJECTION/REGULAR/MONOPHASE/HEAVY BODY - CARTRIDGE

EXAFAST NDS CATALYST: INJECTION/REGULAR/MONOPHASE/HEAVY BODY - CARTRIDGE

Chemical Name: N.A.

PRODUCT USE: Dental Impression Material

The following information is provided with regard to the toxicity and hazards the pure components present in this portion of the unmixed two paste system

=====

 SECTION 2 - HAZARDOUS INGREDIENTS/IDENTITY INFORMATION

COMPONENT AND C.A.S.	EXPOSURE LIMITS	LD50/LC50	%
Silica-Amorphous 112926-00-8	PEL = 10.0 mg/m ³ TLV/TWA = 10.0 mg/m ³ (as dust) (ACGIH)	N.E.	40-50%
Vinyl Dimethyl Poly -Dimethyl Siloxane 68083-19-2	N.E.	N.E.	50-60%

=====

 SECTION 3 - PHYSICAL/CHEMICAL PROPERTIES

BOILING POINT: 160°C SPECIFIC GRAVITY: (H₂O=1) 1.35g/cm³
 VAPOR PRESSURE: 100/50°C MELTING POINT: N.E.
 VAPOR DENSITY: 2.56 EVAPORATION RATE: N.E.
 SOLUBILITY IN WATER: Insoluble ODOR THRESHOLD: N.E.
 COEFFICIENT OF OIL/WATER DISTRIBUTION: N.E.
 APPEARANCE AND ODOR: Blue odorless paste/putty

=====

SECTION 4 - FIRE AND EXPLOSION DATA

FLASH POINT: 252°C closed cup FLAMMABLE LIMITS: N.E.

EXTINGUISHING MEDIA: Dry chemical, carbon dioxide, alcohol foam

SPECIAL FIRE FIGHTING PROCEDURES: Water is not effective medium. Firefighters should wear self contained breathing apparatus and full protective clothing.

UNUSUAL FIRE AND EXPLOSION HAZARDS: Irritating and/or toxic aerosols or gases may be present.

HAZARDOUS COMBUSTION PRODUCTS: Carbon Dioxide, Carbon Monoxide, Sulfur dioxide, Hydrogen Sulfide

=====
SECTION 5 - REACTIVITY DATASTABILITY: STABLE: X UNSTABLE:
POLYMERIZATION: WILL NOT OCCUR: X WILL OCCUR:

CONDITIONS TO AVOID: High temperatures (> 121°C); open flames

INCOMPATIBILITY (MATERIALS TO AVOID): Strong acids, bases, oxidizers.

HAZARDOUS DECOMPOSITION OR BY-PRODUCTS: N.E.

=====
SECTION 6 - HEALTH HAZARD DATA and FIRST AID INFORMATION

	YES	NO	NE	NA	NTP	IARC	OSHA	OTHER
MUTAGENIC AFFECTS:		X						
TERATOGENIC AFFECTS:		X						
REPRODUCTIVE TOXIN:		X						
CARCINOGENICITY:	X			(as Silica dust)		X		
SENSITIZER:		X						

ROUTES OF ENTRY: INHALATION X SKIN X INGESTION X

HEALTH HAZARD: (ACUTE AND CHRONIC): Breathing vapor generated from this product may be irritating to the eyes, nose and throat.

SIGNS AND SYMPTOMS OF OVEREXPOSURE: Headaches

CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE: N.E.
=====

SECTION 9 - PREPARATION INFORMATION

This data is supplied to comply with OSHA Hazard Communication Standard 29 CFR 1910,1200 and W.H.M.I.S. CPR

PREPARED BY: T. Joritz
Director, Regulatory Affairs

Date: 07 March 2001

=====

N.A. = NOT APPLICABLE
N.E. = NOT ESTABLISHED

The information herein is given in good faith but no warranty expressed or implied is made.

=====

		NFPA	
FIRE 1	TOXICITY 1	REACTIVITY 1	SPECIAL -

=====

SECTION 4 - FIRE AND EXPLOSION DATA

FLASH POINT: 252°C closed cup FLAMMABLE LIMITS: N.E.

EXTINGUISHING MEDIA: Dry Chemical, Carbon Dioxide, Alcohol Foam

SPECIAL FIRE FIGHTING PROCEDURES: Water is not effective medium. Firefighters should wear self contained breathing apparatus and full protective clothing.

UNUSUAL FIRE AND EXPLOSION HAZARDS: Irritating and/or toxic aerosols or gases may be present.

HAZARDOUS COMBUSTION PRODUCTS: Carbon Dioxide, Carbon Monoxide, Sulfur Hydrogen Sulfide

=====

SECTION 5 - REACTIVITY DATA

STABILITY: STABLE: X UNSTABLE: POLYMERIZATION: WILL NOT OCCUR: X WILL OCCUR:

CONDITIONS TO AVOID: High temperatures (> 121°C); open flames

INCOMPATIBILITY (MATERIALS TO AVOID): Strong acids, bases, oxidizers.

HAZARDOUS DECOMPOSITION OR BY-PRODUCTS: N.E.

=====

SECTION 6 - HEALTH HAZARD DATA and FIRST AID INFORMATION

	YES	NO	NE	NA	NTP	IARC	OSHA	OTHER
MUTAGENIC AFFECTS:		X						
TERATOGENIC AFFECTS:		X						
REPRODUCTIVE TOXIN:		X						
CARCINOGENICITY:	X				(as Silica dust)		X	
SENSITIZER:		X						

ROUTES OF ENTRY: INHALATION X SKIN X INGESTION X

HEALTH HAZARD: (ACUTE AND CHRONIC): Breathing vapor generated from this product may be irritating to the eyes, nose and throat.

SIGNS AND SYMPTOMS OF OVEREXPOSURE: Headaches

CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE: N.E.

=====

SECTION 6 - HEALTH HAZARD DATA and FIRST AID INFORMATION - continued

EMERGENCY FIRST AID PROCEDURES:

INHALATION: Remove to fresh air if irritation develops

EYES: Flush with large volumes of water, consult a physician if irritation develops.

SKIN: Wash thoroughly with soap and water

INGESTION: Do not induce vomiting. Dilute by drinking several glasses of water. Seek medical attention.

=====

SECTION 7 - PRECAUTIONS FOR SAFE HANDLING AND USE

IN CASE OF RELEASE OR SPILL:

Absorb with inert material; transfer to container for disposal

WASTE DISPOSAL METHOD:

Land fill per local and Federal Regulations

STORAGE, HANDLING, AND SPECIAL PRECAUTIONS:

Store at normal room temperature in a well ventilated area

=====

SECTION 8 - CONTROL MEASURES

RESPIRATORY PROTECTION: N.A.

VENTILATION: LOCAL EXHAUST: Recommended MECHANICAL: N.E.
SPECIAL: N.E. OTHER: N.E.

PROTECTIVE GLOVES: Synthetic/Vinyl Gloves

EYE PROTECTION: Safety glasses or goggles

OTHER PROTECTIVE CLOTHING OR EQUIPMENT: N.E.

WORK/HYGIENIC PRACTICE: N.E.

=====

SECTION 9 - PREPARATION INFORMATION

This data is supplied to comply with OSHA Hazard Communication Standard 29 CFR 1910,1200 and W.H.M.I.S. CPR

PREPARED BY: T. Joritz
Director Regulatory Affairs

Date: 07 March 2001

=====

N.A. = NOT APPLICABLE
N.E. = NOT ESTABLISHED

The information herein is given in good faith but no warranty expressed or implied is made.

=====

		NFPA	
FIRE 1	TOXICITY 1	REACTIVITY 1	SPECIAL -

=====

MATERIAL SAFETY DATA SHEET

SECTION 1 - SOURCE/IDENTITY/USE INFORMATION

MANUFACTURER	SUPPLIER
GC AMERICA INC.	
3737 West 127th St.	
Alsip, Illinois, 60803	
Telephone: 708-597-0900	
Hours: Mon.- Fri. 8:00 am. - 5:00 pm. C.S.T.	
Transportation Emergency No. 800-424-9300	

COMMON NAME:

- EXAFLEX BASE: INJECTION/REGULAR/MONOPHASE/HEAVY BODY
- EXAMIX BASE: INJECTION/REGULAR/MONOPHASE/HEAVY BODY - CARTRIDGE
- EXAMIX NDS BASE: INJECTION/REGULAR/MONOPHASE/HEAVY BODY - CARTRIDGE
- EXAFLEX NDS BASE: INJECTION/REGULAR/MONOPHASE/HEAVY BODY - CARTRIDGE

Chemical Name: N.A.

PRODUCT USE: Dental Impression Material

The following information is provided with regard to the toxicity and hazards the pure components present in this portion of the unmixed two paste system

=====

SECTION 2 - HAZARDOUS INGREDIENTS/IDENTITY INFORMATION

COMPONENT AND C.A.S.	EXPOSURE LIMITS	LD50/LC50	% _____
Silica-Amorphous 112926-00-8	PEL = 10.0 mg/m ³ TLV/TWA = 10.0 mg/m ³ (as dust) (ACGIH)	N.E.	35-55%
Vinyl Dimethyl Poly -Dimethyl Siloxane 68083-19-2	N.E.	N.E.	35-60%
Polydimethyl Siloxane (not listed) (SiH Terminated)	N.E.	LD50= 5mg/m ³ (oral rat) LC50= N.E.	1-20%

=====

SECTION 3 - PHYSICAL/CHEMICAL PROPERTIES

BOILING POINT: 160°C SPECIFIC GRAVITY: (H₂O=1) 1.35g/cm³
 VAPOR PRESSURE: 100/50°C MELTING POINT: N.E.
 VAPOR DENSITY: 2.56 EVAPORATION RATE: N.E.
 SOLUBILITY IN WATER: Insoluble ODOR THRESHOLD: N.E.
 COEFFICIENT OF OIL/WATER DISTRIBUTION: N.E.
 APPEARANCE AND ODOR: Yellow odorless paste/putty

SECTION 4 - FIRE AND EXPLOSION DATA

FLASH POINT: 252°C closed cup FLAMMABLE LIMITS: N.E.

EXTINGUISHING MEDIA: Dry Chemical, Carbon Dioxide, Alcohol Foam

SPECIAL FIRE FIGHTING PROCEDURES:

Water is not effective medium. Firefighters should wear self contained breathing apparatus and full protective clothing.

UNUSUAL FIRE AND EXPLOSION HAZARDS:

Irritating and/or toxic aerosols or gases may be present.

HAZARDOUS COMBUSTION PRODUCTS:

Carbon Dioxide, Carbon Monoxide, Sulfur Hydrogen Sulfide

SECTION 5 - REACTIVITY DATA

STABILITY: STABLE: X UNSTABLE:
 POLYMERIZATION: WILL NOT OCCUR: X WILL OCCUR:

CONDITIONS TO AVOID: High temperatures (> 121°C); open flames

INCOMPATIBILITY (MATERIALS TO AVOID): Strong acids, bases, oxidizers.

HAZARDOUS DECOMPOSITION OR BY-PRODUCTS: N.E.

SECTION 6 - HEALTH HAZARD DATA and FIRST AID INFORMATION

	YES	NO	NE	NA	NTP	IARC	OSHA	OTHER
MUTAGENIC AFFECTS:		X						
TERATOGENIC AFFECTS:		X						
REPRODUCTIVE TOXIN:		X						
CARCINOGENICITY:		X	(as Silica dust)			X		
SENSITIZER:		X						

ROUTES OF ENTRY: INHALATION X SKIN X INGESTION X

SECTION 6 - HEALTH HAZARD DATA and FIRST AID INFORMATION - continued

HEALTH HAZARD: (ACUTE AND CHRONIC): Breathing vapor generated from this product may be irritating to the eyes, nose and throat.

SIGNS AND SYMPTOMS OF OVEREXPOSURE: Headaches

CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE: N.E.

EMERGENCY FIRST AID PROCEDURES:

INHALATION: Remove to fresh air if irritation develops

EYES: Flush with large volumes of water, consult a physician if irritation develops.

SKIN: Wash thoroughly with soap and water

INGESTION: Do not induce vomiting. Dilute by drinking several glasses of water. Seek medical attention.

=====

SECTION 7 - PRECAUTIONS FOR SAFE HANDLING AND USE

IN CASE OF RELEASE OR SPILL:

Absorb with inert material; transfer to container for disposal

WASTE DISPOSAL METHOD:

Land fill per local and Federal Regulations

STORAGE, HANDLING, AND SPECIAL PRECAUTIONS:

Store at normal room temperature in a well ventilated area

=====

SECTION 8 - CONTROL MEASURES

RESPIRATORY PROTECTION: N.A.

VENTILATION: LOCAL EXHAUST: Recommended MECHANICAL: N.E.
SPECIAL: N.E. OTHER: N.E.

PROTECTIVE GLOVES: Synthetic/Vinyl Gloves

EYE PROTECTION: Safety glasses or goggles

OTHER PROTECTIVE CLOTHING OR EQUIPMENT: N.E.

WORK/HYGIENIC PRACTICE: N.E.

=====

SECTION 9 - PREPARATION INFORMATION

This data is supplied to comply with OSHA Hazard Communication Standard 29 CFR 1910,1200 and W.H.M.I.S. CPR

PREPARED BY: T. Joritz
Director Regulatory Affairs

Date: 07 March 2001

=====

N.A. = NOT APPLICABLE
N.E. = NOT ESTABLISHED

The information herein is given in good faith but no warranty expressed or implied is made.

=====

		NFPA	
FIRE 1	TOXICITY 1	REACTIVITY 1	SPECIAL -

=====			

MATERIAL SAFETY DATA SHEET

SECTION 1 - SOURCE/IDENTITY/USE INFORMATION

MANUFACTURER SUPPLIER
 GC AMERICA INC.
 3737 West 127th St.
 Alsip, Illinois, 60803
 Telephone: 708-597-0900
 Hours: Mon.- Fri. 8:00 am. - 5:00 pm. C.S.T.
 Transportation Emergency Telephone No. 800-424-9300

COMMON NAME: EXAFLEX PUTTY BASE AND CATALYST
 EXAFLEX PUTTY BASE AND CATALYST

Chemical Name: N.A.

PRODUCT USE: Dental Impressions

The following information is provided with regard to the toxicity and hazards of the pure components present in this portion of the unmixed two paste system.

 =====
 SECTION 2 - HAZARDOUS INGREDIENTS/IDENTITY INFORMATION

COMPONENT AND C.A.S.	EXPOSURE LIMITS	LD50/LC50	%
Polydimethyl Siloxane (not listed)	N.E.	LD50 = 5mg/m ³ (oral rat)	11%
Vinyl Dimethyl Polydimethyl Siloxane 68083-19-2	N.E.	N.E.	11%
Silicon Dioxide 112926-00-8	PEL = 0.1mg/m ³ TLV/TWA = 0.1mg/m ³ (as dust) (ACGIH)	N.E.	78%

 =====
 SECTION 3 - PHYSICAL/CHEMICAL PROPERTIES

BOILING POINT: 160°C SPECIFIC GRAVITY (H₂O = 1): 1.67
 VAPOR PRESSURE: 100/50°C MELTING POINT: N.E.
 VAPOR DENSITY: 2.56 EVAPORATION RATE: N.E.
 SOLUBILITY IN WATER Insoluble ODOR THRESHOLD: N.A.
 COEFFICIENT OF OIL/WATER DISTRIBUTION: N.E.
 APPEARANCE AND ODOR: A yellow or blue paste. Both are odorless.

=====