



1. Substance / Preparation and Company name

Product Name: Permite C Capsules; Lojic Plus Capsules; GS-80 Capsules, F400 Capsules, New Ultrafine and Ultracaps +

Recommended use: For filling of cavitated teeth by dental professionals.

Manufacturer / Supplier

SDI Limited
5-13 Brunsdon Street, Bayswater
Victoria, 3153, Australia

Telephone:

+61 3 8727 7111 (Business hours)

Southern Dental Industries Ltd
Block 8, St Johns Court
Swords Road
Santy, Dublin, Ireland

Telephone:

+353 1 886 9577 (Business Hours)

SDI Inc.
729 N.Route 83, Suite 315
Bensenville 60106 IL, USA

Telephone:

+630 238 8300 (Business hours)

SDI Brasil Industria e Comercio Ltda
Rua Dr. Virgílio de Carvalho Pinto, 612
Pinheirs, São Paulo, SP, CEP05420-015
Brasil

Telephone:

+(5511) 3031 1700 (Business Hours)

Emergency contact number: +61 3 8727 7111

2. Composition / Information on ingredients

<u>Hazardous ingredients:</u>	<u>Wt. %</u>	<u>CAS No.</u>	<u>EEC No.</u>	<u>Index No.</u>
Compartment 1: Mercury, metallic (40-50% of total product)	100	7439-97-6	231-106-7	080-001-00
Compartment 2: Non toxic alloy powder	100			



3. Hazard Identification:

These products contain mercury. It is toxic if inhaled and acute exposure may cause allergic reactions including dermatitis, digestion and respiratory disorders.

California Prop 65 Warning

This product contains mercury, a chemical known to the State of California to cause birth defects or other reproductive harm.

T

Risk phrases: **23**
33

Toxic
Toxic by inhalation
Danger of cumulative effects

Safety phrases: **1/2**
7
9
45

Keep locked up and out of reach of children
Keep container tightly closed.
Keep container in a well ventilated place.
In case of accident or if you feel unwell, contact a doctor or Poisons Information Centre immediately (show the label where possible).

4. First Aid Measures

General advice: Contains metallic mercury. In case of accident or if you feel unwell, seek medical advice immediately (show label where possible). Danger of cumulative effects.

If inhaled: Toxic by inhalation. Remove to fresh air. Seek medical attention. May cause respiratory disorders including inflammation and fluid retention. Inhalation of mercury vapours at high concentration can cause dyspnea, coughing, fever, severe nausea, vomiting, excess salivation, kidney damage with renal shutdown.

On skin contact: Wash skin with soap and water. Remove contaminated clothing. May cause irritation and allergic reaction.

On contact with eyes: Wash with clear, tepid water. If irritation persists, obtain medical attention. May cause irritation and allergic reaction.

5. Fire Fighting Measures

Suitable extinguishing media: As for adjacent fire.

Special protective equipment: In fires involving large quantities of product, use self-contained breathing apparatus and full protective clothing.

Further information: Hazardous decomposition products may be produced. (Sec. 10).

6. Accidental Release Measures

Spillages: Mercury presents a health hazard if incorrectly handled. Spillages of mercury should be removed immediately, including from places which are difficult to access. Use a plastic syringe to draw it up. Smaller quantities can be covered by sulfur powder and removed. Avoid inhalation of the vapour.



6. Accidental Release Measures Cont'd)

Personal precautions:	Wear appropriate MSHA approved respirator, gloves, safety goggles and protective clothing to prevent skin contact.
Environmental precautions:	Prevent any spillage from entering drains or waterways.
Methods for cleaning up:	Avoid contact with skin and eyes. Pick up with dust pan or method that does not break up mercury into smaller droplets, etc. and contain for disposal.

7. Handling and storage

Handling

Do not breathe powder and avoid exposed mercury surfaces. Wear appropriate gloves, goggles, and protective clothing to prevent skin contact. Wash thoroughly after handling. Keep away from food, drink and around animal feed stuffs.

Storage

Keep container tightly closed and dry. Storage in large quantities (as in warehouse) should be in a ventilated, cool area. Do not store in metal containers. Keep away from sources of ignition and elevated temperatures.

8. Exposure controls and personal protection

8-Hour TWAs:	Mercury - 0.025 mg/m ³ (ACGIH); 0.05 mg/m ³ (Skin) (OSHA/UK & NOHSC/Australia); 1 mg/m ³ (Short term) (Germany);
	Silver - 0.01 mg/m ³ (OSHA/Germany); 0.1 mg/m ³ (ACGIH/U.K. & NOHSC/Australia)
	Tin - 2 mg/m ³ (OSHA/ACGIH/Germany & NOHSC/Australia); 5 mg/m ³ (U.K.);
	Copper - 1 mg/m ³ (OSHA/ACGIH/Germany/UK & NOHSC/Australia)
	Indium - 0.1 mg/m ³ (OSHA/UK & NOHSC/Australia)
	Zinc - 1 mg/m ³ (ACGIH)

These levels are not anticipated under foreseeable use conditions.

Personal protective equipment

Respiratory equipment:	None required under normal use conditions.
Hand protection:	Gloves.
Eye protection:	Safety goggles.

General safety and hygiene measures: Use only as directed. Wash hands after use.



9. Physical and chemical properties

Form and Colour: Silver alloy powder and mercury in separate compartments of a plastic capsule.

Odour:	None
Melting point / melting range:	(Mercury): -38.9°C
Boiling point / boiling range:	(Mercury): 356.6°C
Flash point:	Not available
Explosion limits:	Not available
Ignition temperature:	Not determined
Vapour pressure:	(Mercury) 0.0012 mmHg at 20°C
Specific Gravity:	(Mercury) 13.6 g/cm ³
% Volatiles:	Not applicable
Solubility in water:	Insoluble
Solubility in other solvents:	Insoluble in alcohol
pH value:	Not available
Octanol / water partition coefficient (log POW):	Not determined
Viscosity:	Not determined
Other information:	N/A

10. Stability and Reactivity

Thermal decomposition: No decomposition under normal conditions

Substance(s) to avoid: Strong oxidizers

Hazardous reactions: Mixtures of mercury with acetylene, ammonia, chlorine dioxide, methyl azide, chlorates, nitrates, or hot sulfuric acid can be explosive. Readily amalgamates with most metals.

Hazardous decomposition products: Slightly volatile at room temperature, atmospheric pressure. When exposed to high temperatures, mercury vaporizes to extremely toxic fumes.

11. Toxicological information

Critical hazards to man: Toxic by inhalation. Acute exposure may cause allergic reactions including dermatitis, digestion and respiratory disorders.

Critical hazards to the environment: Not available.

None available regarding product. Some information supplied for ingredient(s).



11. Toxicological information (Cont'd)

LCLo / Inhalation / Rabbit: (Mercury) 29 mg/m³/30 Hour

Chronic Health Effects: Inhalation of mercury vapours, dusts or organic vapours, or skin absorption or mercury over long periods can cause mercurialism. Symptoms include tremors, inflammation of mouth and gums, excessive salivation, stomatitis, blue lines on gums, pain and numbness in extremities, weight loss, mental depression, and nervousness. Exposure may aggravate kidney disorders, chronic respiratory disease and nervous system disorders.

12. Ecological information

None available regarding product.

13. Disposal considerations

Product: Dispose of in accordance with local regulations.

The 1991 Environmental Protection (Duty of Care) Regulations SI No. 2839 and amendments should be noted (United Kingdom).

14. Transport information

These product is not considered to be a dangerous good within the meaning of transportation regulations.

Labelled according to ISO 24234:2004(E) – Mercury and alloys for dental amalgam.

15. Regulatory information

These products are regulated by:

TGA
Medical Devices Directives 93/42/EEC
FDA
National regulations



MATERIAL SAFETY DATA SHEET [according to GHS & NOHSC:2011(2003)]

**Product: PERMITE C CAPSULES; LOJIC PLUS CAPSULES; GS-80 CAPSULES,
F400 CAPSULES, NEW ULTRAFINE AND ULTRACAPS +**

Date / Revised: 31.11.2004

Page 6 of 6

Revision: 3

16. Other information

Preparation of MSDS:

Prepared by: SDI Limited
5-13 Brunsdon Street, Bayswater
Victoria, 3153, Australia

Phone Number:
+61 3 8727 7111

The information contained in the Material Safety Data Sheet is based on data considered to be accurate, however, no warranty is expressed or implied regarding the accuracy of the data or the results to be obtained from the use thereof.

Department issuing MSDS: Research and Development
Contact: Operations Director
